

## CADREX DR 40 SC

Deformation

### DESCRIPTION

**CADREX DR 40 SC** is a chlorine-free, neat oil designed for drawing, bending, reshaping and fine blanking on all ferrous and non-ferrous metals, under low-duty conditions.

### RECOMMENDED APPLICATIONS

For all parts arriving on assembly lines or elements used to make sub-assemblies (sheet steel, bare or coated beforehand with zinc or zinc alloys, sheet aluminum, etc.). Ready to use, it can be used by spraying, brushing or dipping.

### ADVANTAGES

- Does not yellow under an HPRL lamp.
- If it is not rinsed off, **CADREX DR 40 SC** provides temporary protection from all subsequent corrosion, for treated metals.
- Easy to clean before painting application.
- Can protect against corrosion for 1 to 2 months under shelter

### TECHNICAL INFORMATION

CHARACTERISTICS	METHOD	UNIT	CADREX DR 40 SC
Aspect			Limpid
Colour	ASTM D1500		3.5
Density at 20°C	ISO 12.185		0.931
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	39.0
Flash point	ASTM D 92	°C	176
Copper stripe corrosion	NTF M 07105		1a
Pour point	ASTM D 97	°C	-33
Storage			Dry, frost-free space

The specifications are given for information purposes only and may need to change.

### NOTES

Approved by RENAULT, **CADREX DR 40 SC** can be recommended for all subcontractors working for the automotive industry. For severe or deep stamping, use our **CADREX DR 100 SC** and **CADREX DR 220 SC** products respectively.

Specification sheet N° : E2-43-344-R