

## RUBRIC ARCTIC 26

Synthetic Hydraulic Fluids

### DESCRIPTION

**RUBRIC ARCTIC 26** is a high performance hydraulic fluid with a very high viscosity index for all year use in hydraulic equipment operating over a wide temperature range.

### RECOMMENDED APPLICATIONS

High performance hydraulic fluid with a very high viscosity index for all year use in hydraulic equipment operating over a wide temperature range.

### ADVANTAGES

- Allows very good start up performance of hydraulic equipment at very low temperatures.
- Good rust and corrosion protection.
- Very low pour point.
- Zinc-free anti-wear additives for exceptional equipment performance.
- Excellent oxidation stability.
- Outstanding viscosity control over a wide temperature range.

### TECHNICAL INFORMATION

CHARACTERISTICS	Standards	RUBRIC ARCTIC 26	UNIT
Color	ASTM D1500	1	
Viscosity at 40 °C	ASTM D445	26.4	cSt
Viscosity at 100 °C	ASTM D445	8.2	cSt
Viscosity Index	ASTM D2270	310	
Density at 20 °C	ISO 12185	0.871	
Pour Point	ASTM D97	-56	°C
Flash Point	ASTM D92	242	°C
4 ball wear test, wear scar (1h, 40kg)	ISO 20623	0.72	mm
4 ball wear test, weld load	ISO 20623	190	kg
Copper Strip Corrosion	NFT M 07105	1a	

The specifications are given for information purposes only and may need to change.