

SAFCO SPRAY MULTILUBE

Lubrication / Maintenance

DESCRIPTION

10 PURPOSES AEROSOL, BIODEGRADABLE AND NO VOC CONTENT

Penetrating, deoxidizing, anti-humidity, lubricant, degreaser, tar remover, scrubbing, inks thinner, anti-resin, cleaner for plasters and mastics

- Clean, colorless, it is guaranteed silicon and orthophosphoric acid free and contains no chlorinated solvents
- Remove scrubbing, eliminates light or heavy hydrocarbons
- Based on natural plant esters
- No photochemical reactivity
- Non irritating product
- Very low surface tension
- Compatible with all plastic materials and elastomers and do not attack paint.

RECOMMENDED APPLICATIONS

Nuts and bolts, hinges, pins, machine-tool slides degumming, axes, sheathed cables, electromechanical contacts, hinges, guides, columns, rails, telescopic antennas, chains degreasing.

PACKAGING

650 mL Aerosol – pack of 6

USE INSTRUCTIONS

Aerosol under pressure. Protect against sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn even after use.

Do not spray on a flame or incandescent material.

Keep out from children.

Keep away from flames and sources of ignition – Do not smoke.

Shake before use.

Temperature of use: -10 to 220°C

To install the nozzle fitted with an extension, remove the current nozzle well in the axis of the can; do not make lateral movements so as not to damage the seal of the valve.

Aerosol usable in all positions.

ADVANTAGES

- One product for various applications.
- Biodegradable.
- Economical.
- Better corrosion protection.
- Anti-wear
- Without silicone, acids or chlorinated solvents.
- Compatible with all plastics, elastomers and paint.

TECHNICAL INFORMATIONS

CHARACTERISTICS	METHOD	UNIT	SAFCO SPRAY MULTILUBE
Aspect	Visual	-	Clear
Color	Visual	-	Amber
Vapor pressure	-	hPa	< 0.1
Density at 25°C	ISO 12 185	-	0.837
Flash point (closed cup)	NF EN 22719	°C	> 100
Boiling point	-	°C	240
Breakdown voltage	IEC 156	Volts	40 000
Surface tension at 25°C	ISO 6295	Dynes/cm	29.8
Viscosity at 40°C	NF EN ISO 3104	mm²/s	3.3
Salt spray test	NFX 41002	Hour	96
Humidity chamber	ASTM D 2247	Hour	> 140

Measurements made on the active ingredient . The specifications are given for information purposes only and may need to change.

PRECAUTIONS FOR USE

It is essential to consult the safety data sheet before using this product. Remove all ignition points while the product is in use, and in particular avoid using the product on an incandescent body or on a hot surface. Do not use during vapor phase. Avoid all splashing onto cloth to avoid wicking. No smoking. Do not allow the product to leak into the mains drainage system after use. Use in a well-ventilated space.