

# DATA L L L L L L

# SAFKOOL 6110 CS

#### MICRO-EMULSION FOR GRINDING AND MACHINING

# Semi synthetic fluid

## **DESCRIPTION**

**SAFKOOL 6110 CS** is a water emulsifiable metalworking fluid concentrate dedicated for grinding and general machining of cast iron and steel.

Thanks to its formulation **SAFKOOL 6110 CS** maximize the cooling power and minimize the fluid consumption per carry-out.

## **BENEFITS**

- Low foaming product
- Very good cooling and detergency properties
- Good separation of tramp oils
- Very good particles settling properties
- Excellent bio stability and stability in use
- Operator friendly
- Cleanliness of working environment

## **HEALTH & SAFETY**

- Formaldehydes & formaldehydes releasers free
- Boric acid, nitrites and DEA free, without chlorinated additives
- Operator friendly: good dermatological behavior and easy to use

Creation Date: 04/2015 Revision Date: 11/2022






## RECOMMENDED APPLICATIONS & DILUTIONS OF USE

Grinding of cast iron & steel: 3-5%
General machining of cast iron: 4-6%
General machining of steel: 5-8%

The refractometer reading must be multiplied by the refractometer factor to arrive at the real concentration.

## **TECHNICAL INFORMATION**

| TYPICAL<br>CHARACTERISTICS       | UNITS | METHOD     | SAFKOOL 6110 CS |
|----------------------------------|-------|------------|-----------------|
| Appearance                       |       |            | Clear & orange  |
| Density at 20°C                  |       | ISO 12.185 | 1.027           |
| pH at 5%                         |       | NFT 60.193 | 9.7             |
| Break Point Corrosion            | %     | IP 287     | 2.5             |
| Water Hardness range recommended | ppm   |            | 100 - 400       |
| Refractometer Factor             |       |            | 2.0             |



Creation Date: 04/2015 Revision Date: 11/2022



## **INSTRUCTIONS**"

Before first fill, thoroughly clean the installation with an antiseptic such as **Contram CB3**. Drain and rinse the system with water.

If no volumetric mixing system is available, slowly pour **SAFKOOL 6110 CS** into water while stirring continuously to achieve a correct preparation of the emulsion.

To ensure the best quality of emulsion and maximize the fluid efficiency, consult the **Good Practices Handbook - Metalworking Soluble Fluids**.

## SERVICE AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and in-use monitoring of your lubricants. Please contact your technical sales representative

### IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at <a href="https://www.motul.com">www.motul.com</a>

Creation Date: 04/2015 Revision Date: 11/2022